

THE ELIASON® RAPID-MOUNT

The Rapid-Mount is the Choice for Quick & Easy Installation.



RAPID-MOUNT STRIP DOOR

Eliason makes the job of hanging strip doors even easier with our new Rapid-Mount strip door system. The Rapid-Mount design eliminates multiple studs and fasteners, and ensures a simple, fast installation. A 3' x 7' strip door can be installed in a matter of minutes. Simply attach the mounting bracket to the wall, slide the J-Hook Strips into the bracket and install the locking screws at each end to hold the strips in place. No more time-consuming layout, measuring or calculating overlap of strips. Rapid-Mount strips are designed so that the strip overlap is set automatically as you slide them into place.



Eliason Rapid-Mount Strip Doors

product features
& specifications

Quality Engineering Proven Over Time

- The low-profile, extruded aluminum mounting bracket is inherently strong and mounts flush to the wall. Eliason J-Hook strips slide easily into the mounting bracket and can be replaced within minutes when necessary.
- J-Hook strips feature a continuous welded bond and are available in either 6" or 8" widths. The strips are tapered at the top, making installation fast and easy. If the strips ever come unsealed from the J-Hook we guarantee free replacement including freight.
- No need to lay strips out for 24 hours prior to installation. When you are ready to install, just open, hang and you are done! Installation is as easy as 1, 2, 3!
- Applications include retail, supermarket, distribution centers, warehouses, manufacturing, restaurants and cold storage facilities. Specific environments consist of freezer, cooler, personnel, interior, exterior, loading dock and washdown.



Attach the mounting bracket to a flat surface above the opening.



Start at either end and slide the J-Hook portion of the strip into the wall bracket. The ends of the plastic hangers should touch and be flush with the edge of the aluminum wall bracket.



Install a locking screw in each end of the bracket to hold the strips in place and you are done - fast easy!

Specifications

AVAILABLE SIZES:

Model 6602 (6" x .060 thick with a 67% overlap)
Widths – 26", 30", 34", 38", 42", 46", 50", 54", 58",
62", 66", 70", 74", 78", 82", 86", 90", 94", 98"
Maximum Height – 120"

Model 8802 (8" x .080" thick with 50% overlap)
Widths – 26", 32", 38", 44", 50", 56", 62", 68", 74",
80", 86", 92", 98", 104", 110", 116", 122"
Maximum Height – 120"

MATERIAL OPTIONS:

Standard - Our clear PVC strips are designed for use in most walk-in coolers or in doorways at ambient temperatures with personnel, cart, pallet jack and light forklift traffic.

USDA Low Temp - Clear PVC formulated to remain pliable in food service freezer temperatures; also for use in areas where USDA accepted material is required.

Loc-Rib™ - Our standard and USDA grade PVC strips can be fabricated with "locking" ribs to seal against air flow in cooler or freezer temperatures. Ribs also preserve strip clarity by absorbing abrasions. Not available in Model 6602.

Low Temp Reinforced - Nylon reinforced strips remain pliable in freezers subjected to heavy personnel, hand truck or fork lift traffic.



Over 60 Years Strong • www.eliasoncorp.com • (800) 828-3655



9229 SHAVER ROAD, KALAMAZOO, MI 49024 • FAX (800) 828-3577