

SPEC SHEET SR8100

Quote/Order# _____


Company Name: _____

Attention: _____

Email: _____

Phone#: _____

Job Name: _____



Fill in Opening Size in the Blanks Provided Above

STANDARD SPECIFICATIONS: Door body 3/4" exterior grade solid wood core, metal clad. Full height stainless steel panels, both sides. 9" x 14" clear acrylic safety window set in black rubber molding. Door assembly includes mid-rise V-cam hinges, bottom saddle and bottom pin.

INSTALLATION DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations.

SPECIFIC DETAILS FOR DOOR CONSTRUCTION:

WINDOW: Standard 9" X 14" In Black Rubber Molding, Up 60" to Center of Window from Floor
 Other: _____

JAMB GUARD: 11" Polyethylene 11" Polyethylene With Floor Plate 6" Polyethylene
 11" Aluminum 11" Aluminum With Floor Plate 6" Aluminum

PLATE: Specify Height: _____
 Color/Material: Stainless Steel Galvanized Steel Black ABS Other _____

BUMPER: Standard Black Tear Drop Polyethylene, Height: 12 18 24 30 36 42
 Aluminum Bumper Strip:

OTHER SPECIFICATIONS: _____

APPROVED BY: _____

DATE: _____